

PD 527 W

Specifiche Tecniche

Tecnologia Display	DLP™, Digital light processor
Risoluzione nativa	Native XGA (1,024 x 768)
Risoluzione compressa	Maximum SXGA (1,280 x 1,024)
Colori	16.7 Million Colors
Luminosità (ANSI lumens)	3,000 ANSI Lumens (Standard), 2,400 ANSI Lumens (ECO)
Contrasto	2000:1
Rumorosità	32 dBA (Standard mode), 29 dBA (ECO mode)
Peso	2.7Kg (5.9 lbs)
Dimensioni (L x P x H)	283 x 256 x 104 mm (11.1"x 10.1"x 4.09")
Aspect Ratio	4:3 Native, 16:9 Compatible
Compatibilità computer	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards SXGA, SVGA, VGA (resizing)
Compatibilità audio	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)
Throw Ratio	49.9"@2m
Zoom digitale	Yes
Scansione orizzontale	31.5 ~ 100 kHz
Scansione verticale	56 ~ 85 Hz
Distanza di proiezione	3.94' (1.2m) ~ 39.43'(12.02m)
Schermo di proiezione (Diagonale):	25" (0.64m) ~ 300" (7.62m)
Ceiling Mounting Capability	Yes
Keystone Correction	+/-16 Degrees (Vertical)
Audio	One Internal Speaker with 3 watts Output
Durata lampada	2,000 Hours (Standard), 4,000 Hours (ECO)
Tipo lampada	230 W User Replaceable P-VIP Lamp
Alimentazione	AC Input 100-240V auto-switching power supply
Consumo	322 Watts (Operation), 10 Watts (Standby)
Wireless	802.11b/g Wireless Presentation Gateway
Ingressi I/O	HDB 15-Pin D-Sub (VGA/Component/HDTV), 3.5mm Audio Mini Jack, RS232 Connector, 29-pin DVI-I Connector (Digital, HDCP supported), Composite Video RCA Jack, S-Video Mini DIN, 15-Pin D-Sub for Monitor Loop Through, USB Connector for Remote Computer Control, RJ-45 Ethernet Port, 3.5mm Audio Output Mini Jack, Wireless Presentation Gateway Reset Button, Antenna Connector for Detachable Antenna
Accessori	AC Power Cord, VGA Cable (15pin D-Sub), Composite Video Cable (RCA), S-Video Cable, VGA (D-Sub) to Component / HDTV Adapter, USB Cable, Audio Cable (Mini to Mini Phone Jack), Remote Control with Laser Pointer & Mouse & PgUp/PgDn function, Batteries x 2 for Remote Controller, User's Guide (CD-ROM), Quick Start Card, Lens Cap, Carrying Case, Detachable Antenna
Garanzia	All of Acer projectors support a two year carry-in warranty and 90 days for the lamp.



Caratteristiche Principali

- Risoluzione nativa 1024x768
- Contrasto 2000:1
- Luminosità 3000 ANSI lumens
- Tecnologia DLP™

Target Utenti

- Piccole e medie imprese
- Grandi aziende

Punti Chiave

- Funzionalità Wireless
- Zoom digitale, casse integrate
- Ottime performance grazie a luminosità e contrasto elevati
- Connessione digitale

Modello	Part Number	Listino
PD 527 W 2000:1, 1,024 x 768, 3,000 ANSI, 2,7kg, 32db,Digital zoom, DVI in, +/-16° Keystone, 49,9"@2m, da 1,2-12,02m, wireless gateway, 1 speaker 3W integrato	EY.J2701.013	